


TO-46
(CB-10)

X-55 a^o
(CB-76)

X-103^o
(CB-111)
Thyristors - normal series
Thyristors - série normale

Type Type	Case Boîtier	V_{RRM} (V) max.	V_{DRM} (V) max.	$I_{T_{rms}}$ (A) max.	t_{case} (°C) max.	I_{TSM} $t_p = 10$ ms (A) max.	$t_{oper.}$ (°C) min. max.	I_{GT} (mA) $t_{case} = 25$ °C max.	Data sheet in (see page 10) Notice dans (voir page 10)
2N 877	TO-46	30	30	0,5	70	5	-65 +125	0,2	DRT-75
2N 878	TO-46	60	60	0,5	70	5	-65 +125	0,2	DRT-75
2N 879	TO-46	100	100	0,5	70	5	-65 +125	0,2	DRT-75
2N 880	TO-46	150	150	0,5	70	5	-65 +125	0,2	DRT-75
2N 881	TO-46	200	200	0,5	70	5	-65 +125	0,2	DRT-75
BRY 55-30	X-55 a (1)	30 (2)	30 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 55-60	X-55 a (1)	60 (2)	60 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 55-100	X-55 a (1)	100 (2)	100 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 55-200	X-55 a (1)	200 (2)	200 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 55-300	X-55 a (1)	300 (2)	300 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 55-400	X-55 a (1)	400 (2)	400 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-30	TO-46	30 (2)	30 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-60	TO-46	60 (2)	60 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-100	TO-46	100 (2)	100 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-200	TO-46	200 (2)	200 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-300	TO-46	300 (2)	300 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75
BRY 58-400	TO-46	400 (2)	400 (3)	0,6	125 (5)	8	-40 +125	0,2	DRT-75

(1) Can be supplied with P-Strap (X-103) add suffix K.
Peut être livré avec ailette (X-103) ajouter le suffixe K.

(2) V_{RWM} (3) V_{DWM} (4) t_{amb} (5) t_{vj}

○ Plastic case
Boîtier plastique

To be published later
Sera publiée ultérieurement